

LW6020 SPECIFICATIONS

METRIX WALL MOUNTED TOILET

FEATURES:

- Wall mounted, in wall tank toilet
- Vitreous china
- Dual flush consumption (0.8 gpf / 3 lpf or 1.6 gpf / 6 lpf)
- Elongated bowl
- Powerful, quiet flush every time
- Includes soft close seat and lid
- ADA compliant when installed at the required height of 15 1/4" (387mm) - 19 1/4" (489mm)

SPECIFICATIONS:

Water Use:	0.8 gpf (3 lpf) or 1.6 gpf (6 lpf)
Flush System:	Geberit in-wall tank 111.335.00.5 for 2x6 walls Mounting bracket 111.847.00.1 required for 2x6 walls 111.728.00.1 for 2x4 walls Geberit items not included
Min. Water Pressure:	20 psi
Warranty:	One Year Limited Warranty
Material:	Vitreous China
Shipping Weight:	57lbs (26kg)*
Shipping Dimensions:	(LWH) 26" x 18" x 20 1/2" (655mm x 465mm x 520mm)

FINISHES:

White

ACCESSORIES:

- Geberit flush actuator (not included)
- Geberit tank (not included)

CODES / STANDARDS APPLICABLE:

- ADA compliant when installed at the required height of 15 1/4" (387mm) - 19 1/4" (489mm)
- Meets or exceeds ANSI / ASME standard A112.19.2 and CAN / CSA B 45 requirements
- ASME A112.19.2.2003
- IAPMO / UPC / cUPC
- ASME A112.19.5-2005 / CSA B125.3-2005
- CSA B45.0
- CSA B45.1

INSTALLATION NOTES:

Install this product according to the installation guide. Our products must be installed by certified professionals only. Refer to manufacturer and local codes for flush valve requirements.

*Approximate measurements for comparison only.

Note: These dimensions and specifications are subject to change without notice.

